

Product Information

Thermal Transfer Printers



A robust range of universal thermal transfer printers manufactured for industrial applications and offering excellent print definition and mark permanence.

- *200 to 600dpi print quality*
- *Compact and robust housing, with media window*
- *Automatic print positioning*
- *Front graphic display control panel with navigation buttons*
- *Memory card for stand-alone use (non PC reliant)*
- *Ethernet option for printing over network or Internet*
- *Fully compatible with Heatex System of Industrial strength Cable, Core and Panel Marking*
- *Accepts all thermal ribbons and can print on a wide variety of labels including Barcode, Security and everyday thermal transfer labels*

Thermal Transfer Ribbons



A comprehensive range of ribbons designed for use with the Heatex range of industrial strength cable markers to provide excellent mark permanence and legibility.

- *Wax/Resin ribbon - recommended for use on Heatex Core Markers*
- *Resin ribbon - initial clarity of print is not as strong as Wax/Resin but long term durability is much better. Recommended use on Heatex Cable Marker*
- *Wax ribbon - best choice for printing on ordinary paper, coated paper or cardboard*

Thermal Transfer Printers

Industrial strength for robust environments

HEATEX™
SYSTEM

PRINTER				ORDER CODE
CAB A3 UNIVERSAL PRINTER				
- Print Resolution	dpi	203	300	
- Print Speed	mm/sec	200	150	
- Print Width	mm	104	108.4	
- Label Width	mm	120	120	
				360390

* Interface; Parallel IEEE 1284, Serial RS 232, USB Slave

* Optional Interfaces; Ethernet, Twinax-Converter for IBM AS 400 and Coax-Converter for IBM 3270

DIMENSIONS	
H:	274mm
W:	242mm
D:	446mm

WEIGHT
10 kg

POWER REQUIREMENTS
240V

Thermal Transfer Ribbons

Special ribbons for high performance printing

TYPE	WIDTH mm	CORE Ø mm	OUTER Ø mm	METRES	ORDER CODE
Wax/resin	55	25	70	360	379507
Wax/resin	110	25	70	300	356126*
Wax/Resin	110	12.5	35	90	379552
Wax	55	25	70	360	379576
Wax	110	25	70	360	379590
Wax	110	12.5	35	90	379620
Resin	55	25	70	360	379644
Resin	110	25	70	360	379668*
Resin	110	12.5	35	90	379699

* Recommended for Heatex

STANDARD COLOURS
Black

PERFORMANCE *
Mark permanence: MIL-M-81531 BS 3G 198 Part 3 MIL-STD-202

* When used with Heatex computerised marking products and dot matrix printer