

PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference:

OSAG ACRYLIC GLASS SLEEVING (RESIN COATED) 3kV

A class F (155°C) insulating sleeving that exhibits a high degree of flexibility, up to 155°C, combined with high abrasion resistance and mechanical strength.

FEATURES:

- * Strong construction from braided glass.
- * 3.0kV electrical strength.
- * Can be used at 155°C continuously.

ORDERING INFORMATION

Siegrist Part No.	Internal Diameter	Wall Thickness	Coil Size
SAG05	0.5	0.35mm	400m
SAG10	1.0	0.4mm	400m
SAG15	1.5	0.4mm	300m
SAG20	2.0	0.4mm	200m
SAG25	2.5	0.4mm	250m
SAG30	3.0	0.4mm	200m
SAG40	4.0	0.4mm	200m
SAG50	5.0	0.6mm	100m
SAG60	6.0	0.6mm	100m
SAG80	8.0	0.6mm	100m
SAG90	9.0	0.6mm	100m
SAG100	10.0	0.6mm	100m
SAG120	12.0	0.8mm	100m
SAG140	14.0	0.8mm	50m
SAG160	16.0	0.8mm	50m
SAG180	18.0	0.8mm	50m

Typical Properties

Property (units)	Value
Thermal classification	Class F - 155°C
Dielectric strength @ 20°C	3.0kV for 1 minute
Operating Temperature	155°C

Standard Colour availability

Natural, Black, Red, Yellow, Blue

The information contained in this Data Sheet was correct at the time of printing but Siegrist-Orel Ltd reserve the right to alter or amend without notice any of the specifications, dimensions and particulars contained herein and, therefore, customers should ensure that data remains as listed by checking with the company prior to ordering.