

# PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference: **43B**

## OSSG SILICONE COATED BRAIDED GLASS INSULATING SLEEVING

A low-cost, class H (180°C) insulating sleeving, that exhibits a high degree of flexibility over the temperature range - 60°C to + 250°C.

### FEATURES:

- \* 1kV dielectric strength - suitable for lighting units, timers etc.
- \* Capable of use at 180°C continuously, and at 250°C for short periods.
- \* Self extinguishing.

### ORDERING INFORMATION

This material is currently manufactured in the following sizes:-

<b>Siegrist Part No. size</b>	<b>Internal Diameter</b>	<b>Coil</b>
SSG30	3	250m
SSG40	4	100m
SSG60	6	100m
SSG80	8	100m
SSG100	10	50m

### Typical Properties

<b>Property (units)</b>	<b>Value</b>
Thermal classification	Class H - 180°C
Dielectric strength	1kV
Tolerance on bores	± 0.5mm
Operating Temperature	180°C
Maximum short period temperature	250°C

The information contained in this Data Sheet was correct at the time of printing but Siegrist-Orel Ltd reserve the right to alter or amend without notice any of the specifications, dimensions and particulars contained herein and, therefore, customers should ensure that data remains as listed by checking with the company prior to ordering.