

PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference: **40B**

OSVSG VARNISH SATURATED BRAIDED GLASS INSULATING SLEEVING

A class B (130°C) insulating sleeving that exhibits a high degree of flexibility, up to a working temperature of 130°C.

The coating exhibits good abrasion resistance and the sleeving shows virtually no fraying when cut.

FEATURES:

- * 0.8kV dielectric strength.
- * Thin wall allows use in confined spaces.
- * Available in 6 colours.

ORDERING INFORMATION

Siegrist Part No. Size	Internal Diameter	Wall Thickness	Coil
SVSG05	0.5mm	0.4mm	500m
SVSG10	1.0mm	0.4mm	500m
SVSG15	1.5mm	0.4mm	500m
SVSG20	2.0mm	0.4mm	250m
SVSG25	2.5mm	0.4mm	250m
SVSG30	3.0mm	0.4mm	250m
SVSG35	3.5mm	0.4mm	250m
SVSG40	4.0mm	0.4mm	100m
SVSG50	5.0mm	0.6mm	100m
SVSG60	6.0mm	0.6mm	100m
SVSG70	7.0mm	0.6mm	100m
SVSG80	8.0mm	0.6mm	100m
SVSG90	9.0mm	0.6mm	50m
SVSG100	10.0mm	0.6mm	50m
SVSG120	12.0mm	0.6mm	50m
SVSG140	14.0mm	0.6mm	50m

Typical Properties

Property (units)	Value
Thermal classification	Class B - 130°C
Dielectric strength @ 20°C	0.8kV for 1 minute
Operating Temperature	130°C
Maximum short period temperature	450°C (coating will volatilise)
Colour availability	Black, Blue, Brown, Green, Red, Yellow

The information contained in this Data Sheet was correct at the time of printing but Siegrist-Orel Ltd reserve the right to alter or amend without notice any of the specifications, dimensions and particulars contained herein and, therefore, customers should ensure that data remains as listed by checking with the company prior to ordering.