

PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference: **43B**

OSSJ SILICONE COATED BRAIDED GLASS INSULATING SLEEVING

A class H (180°C), insulating sleeving, that exhibits a high degree of flexibility over the temperature range - 60°C to + 250°C, with no significant environmental hazards.

FEATURES:

- * 4kV dielectric strength.
- * Capable of use at 180°C continuously, and at 250°C for short periods.
 - Self extinguishing.

ORDERING INFORMATION:

Siegrist Part No.	Internal Diameter	Wall Thickness	Coil Size
SSJ10	1.0	0.8mm	250m
SSJ15	1.5	0.8mm	250m
SSJ20	2.0	0.8mm	250m
SSJ25	2.5	0.8mm	250m
SSJ30	3.0	0.8mm	250m
SSJ40	4.0	0.8mm	100m
SSJ60	6.0	0.8mm	100m
SSJ80	8.0	0.8mm	100m
SSJ100	10.0	0.9mm	50m
SSJ120	12.0	0.9mm	50m

Standard Colour: Black - Other sizes available

Typical Properties

Property (units)	Value
Thermal classification	Class H - 180°C
Dielectric strength	4kV
Operating Temperature	180°C
Maximum short period temperature	250°C

The information contained in this Data Sheet was correct at the time of printing but Siegrist-Orel Ltd reserve the right to alter or amend without notice any of the specifications, dimensions and particulars contained herein and, therefore, customers should ensure that data remains as listed by checking with the company prior to ordering.