

# PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference: **01N**

## OSC / OSK Neoprene sleeves and markers

**A synthetic rubber material conforming to BS3858 (1965) T. 1, BS3858 (1992) T.1a and BS3G198, Part1, T.1.**

This is a high-grade Neoprene sleeving containing no natural rubbers, yet providing good elasticity and resistance to oils and greases.

OSC Neoprene can be supplied in plain sleeves, or can be cut and printed to customer specification. It is also available as continuous sleeving.

### Typical performance details:-

Temperature Range	: -65°C to + 95°C*
Colour Fastness	: Standard 4 Min.
Fluid resistance	: Acids, Alkalies, Aromatic Fuels, Mineral Oils
Colour availability	: Black, Brown, Red, Orange, Yellow Green, Blue, Violet, Grey, White and Pink.

N.B: Minimum quantities may apply for sizes

above 5mm.

Reference No	C075	C10	C15	C20	C25	C30	C40	C50	C75	C100	C150	C200	C250
Internal Diameter mm	0.75	1	1.5	2	2.5	3	4	5	7.5	10	15	20	25
Std. wall thickness mm	0.5	0.5	0.6	0.6	0.6	0.6	0.65	0.65	0.65	0.65	0.7	0.7	0.7

\*1000 hrs temp. rating (BS3G198. T1) All dimensions given are nominal. Other sizes are available to special order.

**A synthetic rubber material conforming to BS 3858 (1965) T.1, BS 3858 (1992) T.1a and BS 3G198, Part 1, T.1.**

This is the same high-grade Neoprene as described above but to help protect both the sleeve and printing from various fluid degradation a clear overlay is incorporated.

### Typical performance details:-

Temperature Range	: -65°C to + 95°C*
Colour Fastness	: Standard 4 Min.
Fluid resistance	: Acids, Alkalies, Aromatic Fuels, Mineral Oils
Colour availability	: Black, Brown, Red, Orange, Yellow Green, Blue, Violet, Grey, White and Pink.

N.B: Minimum quantities may apply for sizes above 5mm.

Reference No.	K075	K10	K15	K20	K25	K30	K40	K50	K75	K100	K150	K200	K250
Internal Diameter mm	0.75	1	1.5	2	2.5	3	4	5	7.5	10	15	20	25
Std. wall thickness mm	0.5	0.5	0.6	0.6	0.6	0.6	0.65	0.65	0.65	0.65	0.7	0.7	0.7

\*1000 hrs temp. rating (BS3G198. T1) All dimensions are given are nominal. Other sizes available to special order.