

PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference: **03L**

OSF HIGH STRENGTH SILICONE SLEEVES AND MARKERS

A high-strength elastomer conforming to BS 3G198, Part 1, T.4.

FABsil silicone has high tear- strength, good flame-retardant properties and an ability to operate at 250°C for intermittent periods.

It is available in continuous lengths, cut sleeves or as cable markers printed to customer specification.

Typical performance details:-

Temperature Range : -65°C to +250°C
Colour Fastness : Standard 6
Tensile Strength : 8,000 kNm⁻² Min.

Elongation at Break : 400% Min.
Proof Voltage : 8kV per 1mm wall thick.
Insulation Resistance(Dry) : 10,000 Megohms Min.
Colour availability : Black, Brown, Red, Orange, Yellow, Green, Blue, Violet, Grey, White and pink.

N.B: Minimum quantities may apply for sizes above 3mm.

Printed Reference	FM05	FM075	FM10	FM15	FM20	FM25	FM30	FM40	FM50
Plain Reference	FP05	FP075	FP10	FP15	FP20	FP25	FP30	FP40	FP50
Internal Diameter mm	0.5	0.75	1	1.5	2	2.5	3	4	5
Std. Wall thickness mm	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5

All dimensions given are nominal. Other sizes are available to special order.

The information contained in this Data Sheet was correct at the time of printing but Siegrist-Orel Ltd reserve the right to alter or amend without notice any of the specifications, dimensions and particulars contained herein and, therefore, customers should ensure that data remains as listed by checking with the company prior to ordering.