

PRODUCT INFORMATION



IDENTIFICATION AND PROTECTION SYSTEMS

Product Reference: **OS SCM2**

NON-HALOGEN ADHESIVE LINED DUAL WALL POLYOLEFIN

Flexible dual wall tubing, halogen free product with 3:1 shrink ratio. Quick and easy to install with strong adhesive for excellent insulation and complete waterproofing.



Operating temperature: -55 °C to 110 °C

Min. shrink temperature: 90 °C

Shrink ratio: 3:1

Dielectric strength: 21 kV/mm

Standard colours: Black

Encapsulating and anti-corrosion protection of metal pipes. Insulation for communication equipment and cables. Alternative to taping in medium voltage applications.

SCM2	Expanded(mm) (min.)	Inside Dia. (mm) (outer layer only)	Recovered(max.) (not guaranteed)	Wall Thickness (mm) Recovered	Quantity(m) per Bag/ Box
04	10.2	3.80	2.30	1.50	12/120
07	19	5.60	4.10	2.00	12/120
11	28.0	9.5	6.5	2.00	12/60
13	33.0	10.2	7.8	2.00	12/60
15	38.1	12.7	10.3	2.30	12/48
17	44.0	14.0	11.6	2.30	12/48
20	52.1	18.2	15.8	2.30	6/30
27	70.0	25.5	23.1	2.30	6/24
35	90.0	30.0	27.6	2.50	3.6/18
50	125.0	40.0	37.6	2.50	2.4/24

The information contained in this Data Sheet was correct at the time of printing but Siegrist-Orel Ltd reserve the right to alter or amend without notice any of the specifications, dimensions and particulars contained herein and, therefore, customers should ensure that data remains as listed by checking with the company prior to ordering.